

Impact of Storm Louis on two Spanish harbours: a multi-~~platformsensor~~ approach

Pablo Lorente¹, Garbiñe Ayensa², Marta De Alfonso¹, Samuel Galán¹, Pilar Gil¹, Fernando Manzano¹, Anna Magdalena Matulka¹, Pedro Montero², Verónica Morales-Márquez¹, Begoña Pérez-Gómez¹, Cristina Pérez-Íñigo¹, Susana Pérez-Rubio¹ and M. Isabel Ruiz¹

¹Puertos del Estado, Madrid, 28042, Spain

²INTECMAR (Instituto Tecnológico para o Control do Medio Mariño de Galicia), Vilagarcía de Arousa, 36611, Spain

Correspondence to: Pablo Lorente (plorente@puertos.es)

Abstract

Storm Louis struck south-western Europe between 22 and 26 February 2024, producing severe meteocean conditions that led to significant disruptions in transportation networks, widespread power outages and one confirmed fatality. This high-impact event exemplified the growing threat that deep extratropical cyclones pose to European coastal infrastructure. The synoptic-scale characteristics of Storm Louis were examined using ERA5 reanalysis data, revealing a marked Azores High-Iceland Low ~~pressure~~ dipole configuration, indicative of the canonical manifestation of the positive phase of the North Atlantic Oscillation. A strong SW-NE pressure gradient gave rise to persistent and anomalously intense north-westerly ~~maritime-~~~~polar~~ winds over the northeastern Atlantic Ocean ~~and the Iberian Peninsula~~ that induced significant waves heights above 8 m. The concurrent impact on two geographically distant Spanish ports – Langosteira in the northwestern Iberian (NWI) region and Tarragona in the northeastern Iberian (NEI) region – was evaluated using a multi-~~platformsensor~~ observational framework that integrates *in situ* measurements from four ~~moored~~ buoys and two tide gauges with remotely-sensed data provided by two High Frequency Radar (HFR) systems. In the NWI (NEI) area, multiple observed wind and wave parameters associated with Storm Louis exceeded the 99.9th (99th) ~~climatological~~~~historical~~ percentiles, based on ~~the available~~ 11-year ~~observational record~~~~reference~~ period spanning 2014-2024. Analysis of high-frequency sea level oscillations, recorded by tide-gauges at both ports during Storm Louis, revealed contrasting wave-induced agitation responses between Langosteira and Tarragona harbours, despite exceedance of their respective historical 99th percentile threshold. The former experienced a moderate but prolonged (33 h long) event peaking at 0.68 m with minimal storm surge influence, while the latter underwent a shorter (16 h long), more intense peak of 1.77 m, also decoupled from storm surge. Over the 2014-2024 period, the relationship between offshore wave parameters and inner-harbour agitation was explored to isolate the open-ocean conditions most strongly associated with critical in-port sea states likely to compromise maritime operations. Results revealed significantly high linear correlations between offshore wave height conditions and harbour agitation ($R = 0.88$ for Langosteira, $R = 0.75$ for Tarragona). However, Tarragona harbour exhibited a more complex, bimodal directional response: peak agitation events were predominantly associated with moderate offshore wave heights (< 3 m) propagating from the southernmost sector, underscoring the harbour's marked sensitivity to wave incidence angle and its role in amplifying internal hydrodynamic response. Finally, HFR wave data, validated against buoy observations, reliably

captured storm-induced waves, highlighting their value for real-time extreme hazard assessment and climate-resilient port infrastructure.

1 Introduction

The genesis of deep extratropical cyclones over central Europe is governed by a complex interplay of synoptic-scale atmospheric and oceanic factors (Mohr et al., 2020). These systems commonly emerge when warm, moisture-laden air advected from the Mediterranean or North Atlantic converges with cold and dry continental air masses of Arctic or Siberian origin. The resulting sharp thermal and moisture gradients create atmospheric instability: as the warm air ascends and the colder air descends, a low-pressure centre forms, making the region susceptible to highly dynamic and rapidly evolving weather conditions. Such systems are often associated with intense windstorms, heavy precipitation, and, in some cases, catastrophic flooding, particularly during the winter season (Álvarez-Fanjul et al., 2022; Owen et al., 2021; Jacobeit et al., 2006; Wanner et al., 2004).

The socio-economic relevance of extreme extratropical cyclones has become increasingly prominent in recent decades, particularly in the context of anthropogenic climate change, ~~which is projected~~ to alter their frequency, intensity, and spatial distribution (Khodayar et al., 2025; Cao and Su, 2025; Kleespies et al., 2024; Konisky et al., 2015). These high-impact events have exposed the structural vulnerabilities of western Europe, highlighting the substantial risk posed to critical infrastructure, human assets, and regional economies (Leal Filho et al., 2024; Mateos et al., 2023; Forzieri et al., 2018). For instance, Storm Kyrill (17–19 January 2007) produced hurricane-force winds across large areas of Europe, resulting in fatalities and generating the highest insured storm losses recorded in Europe to date (Kettle, 2023; Fink et al., 2009). Similarly, Storm Klaus (23–24 January 2009) caused 26 direct fatalities while impacting northern Iberia and southern France, with more than 715,000 insurance claims filed and total losses exceeding USD 6.0 billion, ranking it as the costliest weather-related disaster globally that year (Liberato et al., 2011; Aon Benfield, 2010). Storm Gloria (19–24 January 2020) caused several casualties and multi-million damages in susceptible coastal areas of Eastern Spain (Álvarez-Fanjul et al., 2022). ~~More recently, Storm Ciara (8–9 February 2020) affected the British Isles, resulting in estimated insured losses of approximately GBP 200 million (Jardine et al., 2023).~~ These events illustrate the mounting economic burden of windstorms under current climatic conditions and underscore the urgency of improved risk assessment, adaptation strategies, and early warning systems.

Severe sea states associated with extreme storm events can significantly disrupt port operations and damage coastal infrastructure, particularly in vulnerable locations such as deltas, low-lying areas, and erosion-prone shorelines (Lucio et al., 2024). Given their strategic role as logistic hubs within maritime transport networks, international supply chains and global trade, ports are critical economic assets (Verschuur et al., 2022). Consequently, storm-induced disruptions can result in substantial financial losses, not only from direct damages and operational delays but also from reputational impacts in an increasingly competitive global marketplace (Verschuur et al., 2023).

In recent years, extensive research has focused on assessing the vulnerability of port infrastructure to extreme weather, advancing climate risk analyses and formulating adaptation strategies within the Spanish port system (Fernández-Pérez et al., 2024; Portillo Juan et al., 2022; Izaguirre et al., 2021; Camus et al., 2019; Sánchez-Arcilla et al., 2016). At the global scale, a comprehensive survey by Asariotis et al. (2017), encompassing port authorities in 29 countries across all world regions, reported that approximately 70% of respondents had experienced weather-related disruptions. These included impacts on operations (76%), delays (60%), and physical damage (45%). The most frequently cited climatic stressors - ranked in decreasing order - were strong winds, heavy precipitation, storm surges, fog, and wave penetration.

While high wind speeds can severely hinder crane operations and cargo handling efficiency within port terminals (Piñeres-Castillo et al., 2024), the operability of vessels is predominantly governed by the energy and directionality of incident offshore waves penetrating into the port basin, where they interact with complex bathymetry, harbour geometries, and structural elements (Romano-Moreno et al., 2022; Sierra et al., 2015 and 2023). The resulting intra-harbour wave dynamics - commonly referred to as *wave agitation* - can significantly degrade operational efficiency and compromise safety margins. Excessive wave agitation amplifies vessel motions at berth, increasing the risk of mooring line failures and vessel-structure collisions, with potential damage to both ships and port infrastructure (Díaz-Hernández et al., 2021).

In this context, the precise monitoring and comprehensive understanding of extreme weather-related hazards are essential not only for the implementation of effective prevention strategies and the informed management of port operations, but also for strengthening the socio-ecological resilience of coastal communities (Linnenluecke et al., 2012). The present study focuses on the characterization of Storm Louis, which was associated with a deep low-pressure system (Fig. 1a) that traversed the North Atlantic, delivering severe weather conditions across large areas of western Europe between 22 and 26 February 2024.

The storm was marked by intense rainfall and powerful winds (Fig. 1b), with sustained gusts exceeding $20 \text{ m}\cdot\text{s}^{-1}$ that caused widespread disruptions including transportation delays, power outages, and one fatality reported in France. In Spain, the event was officially classified by the State Meteorological Agency (AEMET) as a high-impact storm, reflecting wind gusts locally exceeding $140 \text{ km}\cdot\text{h}^{-1}$ and the generation of extreme sea states (AEMET website, 2025). From an oceanographic standpoint, the north-westerly winds accompanying the storm generated ~~signifieant-pronounced~~ swell, with significant wave heights in the range 6-8 m and local maxima exceeding 8 meters (Fig. 1c), which severely impacted the Galician and Cantabrian coastlines (NW Iberia region) and, more specifically, Langosteira harbour (Fig. 1d and Fig. A1a). Additionally, harsh metocean conditions were also observed in NE Iberia: strong southeasterly winds (above $12 \text{ m}\cdot\text{s}^{-1}$, Fig. 1b) induced high waves that easily penetrated into Tarragona harbour due to its mouth orientation (Fig. 1e and Fig. A1b). While these conditions may have challenged port operations at the entrance, no operational disruptions were officially reported along the piers, handicapping port operations.

The signature of Storm Louis was investigated through a multi-~~platformsensor~~ observational framework, integrating both *in situ* instruments - four directional wave moored buoys and two tide gauges - and a remote sensing technology - two High Frequency Radars Networks (hereinafter, HFR) - to capture the storm's concurrent impact on two geographically distant Spanish harbours, located in the northwestern and northeastern Iberia areas, respectively (NWI and NEI, in Fig. 1a). A key

novelty of this work lies in the integrated use of these complementary observational platforms, which allows a comprehensive, cross-scale characterization of storm-driven harbour impacts (Davidson et al., 2019; Tintoré et al., 2019). This approach enabled a detailed assessment of the relationship between offshore wave characteristics and the resulting sea state within each harbour domain. The analysis aimed to identify which open-ocean conditions are most likely to trigger hazardous port conditions, potentially disrupting maritime operations and compromising the cost-time efficiency of port logistics (Lorente et al., 2024; Romano-Moreno et al., 2022; Díaz-Hernández et al., 2021; Sierra et al., 2015 and 2023). As a secondary objective, the performance of both ~~HFR~~High-Frequency-Radar networks(HFR)-systems in accurately monitoring extreme offshore wave conditions during Storm Louis was quantitatively assessed. While this land-based remote sensing technology has achieved global recognition for its capability to deliver reliable, near real-time, two-dimensional surface current maps (Roarty et al., 2019; Rubio et al., 2017), its application for wave field characterization remains relatively limited within operational oceanography, with most studies confined to academic research settings (Morales-Márquez et al., 2024; Saviano et al., 2022; Lorente et al., 2022; López et al., 2019; Wyatt et al., 2005; Wyatt, 1986). To address this gap, a skill assessment was conducted by comparing HFR-derived wave parameters against *in situ* wave measurements from ~~moored~~wave buoys located within the HFR coverage area. This evaluation aimed to enhance confidence in the use of HFR ~~networks~~systems for monitoring extreme wave events, thereby supporting their integration into operational coastal hazard forecasting and maritime risk management frameworks (Basañez et al., 2019; Atan et al., 2015 and 2016). This work is structured as follows: Section 2 outlines the observational and modelled data sources. Section 3 describes the methodology adopted. Results are presented and discussed in Section 4. Finally, principal conclusions are drawn in Section 5.

2 Data

All modelled and observational datasets employed in this study are summarized in Table 1 and Table 2 and are briefly described below. While some *in situ* instruments were deployed prior to 2014, the observational time series were standardised to the 2014–2024 period for consistency reasons, as the collection of directional wave data by Langosteira coastal buoy started on June 2013 (Table 3).

2.1 ERA5 reanalysis

ERA5, the fifth-generation reanalysis for the global climate and weather produced by the European Centre for Medium-Range Weather Forecasts (ECMWF), provides high-resolution, consistent, and quality-controlled datasets extending back to 1940 (Product ref. No. 1 in Table 1). ERA5 offers hourly estimates of a wide range of atmospheric and oceanic variables, which are regridded, respectively, to a regular 0.25° and 0.5° horizontal grid. Synoptic-scale analyses of daily-averaged fields of sea level pressure (SLP), 10-meter wind speed (W10), significant wave height (SWH), and mean wave direction

(MWD) were conducted over the North Atlantic domain (40°W-20°E, 20°N-70°N) to characterize the dominant metocean features during the peak phase of Storm Louis (Table 2, No. 1).

2.2 *In situ* moored buoys

Two deep-water and two coastal moored buoys, operated by Puertos del Estado, were utilized in this study (Fig. 1d-e, and Fig. A1). These *in situ* observational platforms provide quality-controlled, hourly-averaged measurements of a range of oceanographic parameters (Product ref. No. 2 in Table 1), including SWH, MWD, wave period at spectral peak (or peak wave period: PWP) and mean wave period -MWP- (Table 2, No. 2 and No. 3). Additionally, deep-water moored buoys also provide hourly-averaged estimations of atmospheric parameters (SLP and wind). Comprehensive technical specifications for each buoy are detailed in Table 3.

The quality control, defined by the Copernicus Marine Service *in situ* team (Copernicus Marine *In situ* Team, 2020), was based on a battery of automatic checks performed in real time to flag and subsequently filter inconsistent values: the spike test, stuck value check, or rate of change on time, among others.

2.3 Tide-gauges

Two radar tide gauges, manufactured by Miros and operated by Puertos del Estado as part of the REDMAR network (Pérez-Gómez et al., 2014), have been deployed at the mouth of Langosteira (Fig. 1d and Fig. A1a) and Tarragona (Fig. 1e and Fig. A1b) harbours since November 2012 and May 2011, respectively (Table 4). These sensors deliver quality-controlled sea level measurements at a sampling rate of 2 Hz (Product ref. No. 3, Table 1), facilitating the analysis of high-frequency oscillations such as meteotsunamis and infragravity waves (García-Valdecasas et al., 2021). Additionally, 20-minute averaged estimates of port agitation - defined as port-scale oscillations induced by incoming wind waves with periods shorter than 30 s - were derived using an 8th-order Butterworth high-pass digital filter with a cut-off frequency of 1/30 Hz. The resulting agitation time series were subsampled to hourly intervals (Table 2, No. 3) for subsequent analysis:

- i) over the period 20-29 February 2024 to evaluate harbour response under extreme weather conditions. Complementarily, hourly storm surge estimates (i.e., meteorological residuals) were examined to assess their potential contribution on wave-induced agitation during Storm Louis.
- ii) over the 11-year observational record period spanning 2014-2024, to investigate the relationship between offshore energetic wave conditions and the sea state within both harbours, with a focus on the directional dependencies influencing wave penetration and the resulting agitation response.

2.4 High Frequency Radars (HFR)

Two 'direction-finding' SeaSonde HFR networks (Barrick, 1977), manufactured by CODAR Ocean Sensors, were employed in this study (Table 5). While the first one (composed by 5 sites) was deployed along the Northwestern Iberian Peninsula (HFR-GaliciaNWP) in July 2010, the second one (formed by 3 sites) was installed in the Northeastern Iberian Peninsula

(HFR-DeltaEbroNEI) in December 2013. The geographical distribution of the radar stations is shown in Fig. 1d and Fig. 1e, respectively.

In both study regions, the HFR installations provide wide and unobstructed coverage, ensuring stable and reliable directional solutions. In the case of HFR-Galicia network, all HFR sites are installed at lighthouse locations, which offer elevated, exposed positions with clear line-of-sight over the ocean and minimal physical obstructions. In the HFR-DeltaEbro network, the HFR sites are deployed within a protected natural area, where infrastructure is limited and the surrounding environment is well preserved, resulting in minimal electromagnetic or physical interference. These site characteristics ensure favourable geometric configurations and stable directional performance for wave retrieval in both regions.

Each network provides half-hourly wave observations (Product ref. No. 4, Table 1) - including SWH, centroid wave period (CWP), and MWD - retrieved in near real time across multiple annular rings (circular concentric range arcs) extending radially from each onshore radar site (Fig. A2). For this study, HFR-derived wave measurements were subsampled to 60-minute intervals (Table 2, No. 4) to ensure temporal consistency across datasets, enabling not only the investigation of wave conditions during storm Louis but also a robust long-term skill assessment over the period 2014–2024.

3 Methodology

3.1 Characterization of Storm Louis

To elucidate the driving mechanisms underlying the development of Storm Louis, the prevailing atmospheric conditions were briefly examined at the synoptic scale, with particular emphasis on daily mean fields of SLP and W10-fields. This analysis aimed to identify the large-scale barometric patterns, pressure gradients, and wind structures that contributed to the storm's intensification, thereby enabling a better understanding of the meteorological forcing responsible for the observed oceanographic impacts, especially within the affected harbour environments.

Recognizing the interconnected nature of hydrodynamic variables, an isolated analysis of individual extremes was deemed inadequate to capture the full spatial and temporal footprint of Storm Louis. Instead, a percentile-based statistical framework was employed to characterize the tail behaviour of key environmental variables, including W10, SWH and, MWP and port agitation, among others. The 1st, 5th, 25th, 50th, 75th, 90th, 95th, 99th and P99.9th historical percentiles (P1, P5, P25, P50, P75, P90, P95, P99 and P99.9, hereinafter) were derived from an 11-year (2014-2024) observational dataset to contextualize storm Louis within its broader climatological distribution (Coles, 2001). These high-impact thresholds may serve as operational benchmarks for impact-based analysis, facilitating the identification of critical exceedance frequencies relevant to risk assessment and port operational management. Notably, similar percentile-based thresholds have been previously proposed in the context of coastal storm characterization by Harley (2017), Morales-Márquez et al. (2020) and Fanti et al. (2023). In the specific case of port agitation, historical percentiles were intended as purely statistical indicators of anomalous harbour response, rather than direct representations of formal operational limits applied by port authorities.

Hourly estimations of storm surge component (meteorological residuals) were analysed to assess their potential contribution to the pronounced increase in harbour agitation observed during storm Louis. This evaluation aimed to determine whether elevated water levels played a significant role in amplifying the port response under storm conditions. In this context, connected extremes are of particular concern for harbour operability. Their combined impacts can interact nonlinearly, resulting in synergistic effects that pose a greater threat to port infrastructure than isolated extreme events (Velpuri et al., 2023).

The long-term relationship between energetic offshore wave conditions (SWH, MWP and MWD) and port agitation was analysed to assess directional dependencies and harbour response under extreme forcing scenarios, as the direction of the most energetic incoming waves may be critical to harbour impacts. Scatterplots were thereby computed to infer the dependence between port agitation and offshore SWH data.

In addition, the monthly distribution of extreme hourly agitation events - defined as values exceeding the P90, P95, and P99 thresholds - was derived from the 11-year observational time series provided by Langosteira (NWI) and Tarragona (NEI) tide-gauges. This analysis aimed to identify potential seasonal patterns or preferential timing in the occurrence of high-agitation conditions, thereby providing insight into whether certain phases of the annual cycle are more prone to operational disruptions due to extreme metocean forcing.

3.2 HFR: fundamentals and data treatment

The HFR land-based remote sensing technology is based on measurements of the radiowave-backscattered signal from ocean surface gravity waves in the 3–30 MHz range of the electromagnetic spectrum (Crombie, 1955). CODAR SeaSonde “direction-finding” HFR ~~networks~~ systems measure the return signal continuously over all angles, exploiting the directional properties of a collocated three-element receive antenna system to infer the direction of the incoming signals (Barrick et al., 1977).

While fine-resolution maps of the surface circulation are obtained from the Doppler shift of the predominant first-order peaks in the sea-echo Doppler spectrum, wave parameters are deduced from the weaker and noisier second-order peaks. The second-order scattering-based methods significantly rely on the echo quality, which varies with sea state and radar frequency (Wyatt et al., 2005). The relative contribution of the second-order spectrum increases with both the radar frequency and the wave height. Since wave data are dependent upon the occurrence of both Bragg and larger surface gravity waves. There is a minimum threshold for sea states at a given radar frequency in which reliable wave parameters can be determined. Below such a sensitivity threshold, the lower-energy second-order spectrum is closer to the noise floor and more likely to be contaminated with spurious contributions that might result in wave height overestimation or limited temporal continuity in wave measurements (Tian et al., 2017; Lipa et al., 2018; Lipa and Nyden, 2005). During extreme weather events, there is also a limiting factor for HFR accuracy as the wave height increases and exceeds the saturation limit defined (on an inverse proportion) by the radar transmit frequency. If the radar spectrum saturates, the first and second-order peaks merge and

225 interpretation of the spectra becomes impossible with existing methods (Forney et al., 2015). It is worth mentioning that theoretical upper performance thresholds for each HFR system (Table 5), were not exceeded during storm Louis.

HFR directional wave spectrum and derived parameters (SWH, CWP and MWD) can be determined from the weaker second-order sea-echo Doppler spectrum by adopting two main approaches: full integral inversion or fitting with a model of ocean wave spectrum (Lipa and Nyden, 2005). A variety of inverse techniques have been developed over the last decades

230 (Barrick, 1977; Wyatt, 1990; Hisaki, 2006). The wave parameters used in this study, based on 30 min averaged backscatter data, were obtained directly by the CODAR radar proprietary software: [the SeaSonde Radial Suite Software Release 7 \(R7\). This wave processing tool](#) which performs a least square fitting technique between the second-order radar spectrum and a Pierson-Moskowitz with cardioid directional function model. Specifically, SeaSonde HFR [networks](#) measure a wave period that represents the centroid of the model being fitted to the second-order Doppler spectrum (Lipa and Nyden, 2005),

235 hence hereafter referred to as the centroid wave period (CWP).

HFR wave data were collected in near real-time, assuming the homogeneity over the whole of each range cell (RC). Specifically, each site composing HFR-[GaliciaNW](#) system has 5 individual RCs (5.1 km wide), which extended radially from an origin at the onshore radar site to a distance 25.5 km offshore (Fig. A2a). Each site from HFR-[DeltaEbroNE](#) presents 7 RCs (1.66 km wide) which extended radially from an origin at the onshore radar site to a distance 11.62 km

240 offshore (Fig. A2b). While the returned signal might be too weak for the outermost RCs, shallow water effects can become significant for innermost RCs, impacting also on radar sea-echo (Lipa et al. 2008). Therefore, we selected the intermediate RC that recorded the highest percentage of valid data, based on the same quality control procedures previously applied to the *in situ* wave observations. Accordingly, RC3 from [VILLAVillano](#)-site (HFR-[GaliciaNW](#)) and RC4 from [ALFAAlfacada](#)-site (HFR-[DeltaEbroNE](#)) were selected for comparison with *in situ* wave observations from Villano-Sisargas and Tarragona

245 [moored](#) buoys, respectively, in order to evaluate HFR accuracy to capture extreme offshore wave conditions (Fig. A2). The selected sites were those closest to their corresponding deep-water [moored](#) buoys and/or exhibited the highest wave data availability throughout the lifecycle of Storm Louis.

Finally, the statistical metrics used in the present study to compare two data sets included the mean, the standard deviation – σ –, the root mean squared error - RMSE - and the Pearson correlation coefficient - R - (Emery and Thompson, 2001).

250 4 Results

4.1 Analysis of [s](#)Storm Louis

The large-scale synoptic conditions associated with Storm Louis were characterized using [daily-averaged](#) ERA5 reanalysis data for SLP, W10 and SWH (Fig. 1a-c). The prevailing SLP pattern featured a classic dipole structure, consisting of a persistent subtropical high ([~1035 hPa](#)) over the southwestern North Atlantic and a deep low ([~968 hPa](#)) centred over

255 northeastern Europe (Fig. 1a). This configuration, commonly referred to as the Azores High–Icelandic Low dipole, is a key

expression of the North Atlantic Oscillation, a dominant mode of atmospheric variability modulating storm tracks and weather extremes across the North Atlantic sector (Hurrell and Deser, 2009). During the peak phase of the storm (23 February 2024), the pressure gradient exceeded $1.7 \text{ Pa} \cdot \text{km}^{-1}$ and was oriented along a southwest–northeast axis, promoting sustained north-westerly winds with velocities surpassing $18 \text{ m} \cdot \text{s}^{-1}$ over the northeastern Atlantic (Fig. 1b). These intense

winds generated high-energy swell systems with SWH exceeding 8 m (Fig. 1c).

In particular, the NWI study area (Fig. 1d) and Langosteira harbour (Fig. A1a) experienced substantial wave impact and atmospheric pressure anomalies. The Villano-Sisargas deep-water buoy recorded a cumulative SLP drop of 33 hPa between 20–25 February, reaching a minimum of 1000 hPa (Fig. 2a), a value slightly below the P5 threshold derived from the 2014–2024 reference period climatology (Fig. 2b). Concurrently, peak offshore wind speeds reached $17.57 \text{ m} \cdot \text{s}^{-1}$, exceeding the local P99.9 percentile (Fig. 2c). Langosteira coastal buoy detected extremely energetic sea states from the northwest (Fig. 1d), with a peak SWH of 8.44 m and a peak MWP of 13.7 s recorded on 24 February (Fig. 2a). Notably, the P99.9 threshold of SWH (8.04 m) was occasionally exceeded during two non-consecutive hours, while the observed MWP fairly surpassed the P99.9 level (12.0 s), nearly matching the all-time maximum value of 13.9 s recorded during the 2014–2024 reference period (Fig. 2d).

Severe oceanographic conditions were also observed in the NEI study area (Fig. 1e). Near Tarragona Harbour (Fig. A1b), the deep-water buoy recorded a SLP minimum of 999 hPa (Fig. 2e), approaching the P1 threshold for the region (Fig. 2f). Offshore wind speeds peaked at $14.29 \text{ m} \cdot \text{s}^{-1}$, exceeding the local P99 (Fig. 2g). The Tarragona coastal buoy recorded high waves coming from the southernmost sector (Fig. 1e), with SWH and MWP peaking at 1.67 m and 6.04 s, respectively, during the early hours of 26 February (Fig. 2e). These values were close to or marginally above the P99 thresholds for the corresponding wave parameters (Fig. 2h).

4.2 Sea state within two harbours

Hourly time series of the storm surge component (meteorological residuals) and port wave agitation, measured during the full lifecycle of storm Louis at Langosteira (NWI area) and Tarragona (NEI area) tide-gauges, are presented in Fig. 3a and Fig. 3b, respectively. While both sites experienced high wave agitation above historical P99 thresholds, the intensity and temporal structure of these events differed substantially. Langosteira tide-gauge displayed a moderate but prolonged agitation episode, reaching a peak of 0.68 m on 24 February afternoon (Fig. 3a). The P99 threshold for the 2014–2024 period (set to 0.52 m) was slightly surpassed for 33 non-consecutive hours. The storm surge component remained relatively subdued throughout the event, with fluctuations mostly below 0.50 m, and no clear peak coinciding with the maximum agitation. By contrast, Tarragona tide-gauge captured an intense and short-lived event, peaking at 1.77 m on early 26 February 2024 (Fig. 3b). The local P99 threshold for the 2014–2024 period (set to 1.20 m) was far exceeded for 16 consecutive hours. The storm surge signal at Tarragona tide-gauge remained modest, with magnitudes generally under 0.3 m, exhibiting minimal correlation with the agitation peak, consistent with a wave-driven dynamic.

290 These contrasting behaviours can be interpreted within a multi-scale framework linking large-scale wave generation to local
harbour response. Wave energy generated in the North Atlantic required finite time to propagate toward the regional offshore
domains and underwent directional evolution before interacting with each harbour. At the local scale, harbour agitation did
not respond instantaneously to offshore wave forcing; rather, it was strongly modulated by site-specific factors, including
directional sensitivity, wave transformation processes at the harbour entrance, and intrinsic response times associated with
wave–structure interactions. Processes such as diffraction and reflection within the harbour basins played a key role in
shaping both the magnitude and temporal persistence of the observed agitation, thereby explaining the pronounced
295 differences between the two sites despite their exposure to the same synoptic-scale storm event.

Hourly scatter plot analyses conducted over the 11-year study period (2014–2024) revealed a strong statistical correlation between offshore wave conditions and internal harbour agitation across both study sites (Fig. 3c-f). Linear regression analysis of the SWH against harbour agitation yielded significantly high correlation coefficients, specifically $R=0.88$ for Langosteira harbour and $R=0.75$ for Tarragona harbour. In the case of Langosteira harbour (Fig. 3c-d), a total of 743 hourly records exceeded the P99 agitation threshold (0.52 m). Of these, the 100% were associated with MWP above 6 s and incident wave directions within the prevailing sector 295° – 360° (clockwise from true north). By contrast, the scatter plot for Tarragona harbour exhibited a more complex, bimodal directional response (Fig. 3e-f). Despite the highest offshore SWH (>3 m) and MWP (>7 s) values being observed from wave directions between 90° and 120° , these did not correspond to peak agitation events within the port basin. Instead, agitation events exceeding 2 m were predominantly driven by moderate offshore wave heights (~ 2 – 3 m), associated with MWP values in the range 5–7 s, penetrating from the southernmost sector (150° – 210°). This indicates a pronounced sensitivity of the harbour's internal hydrodynamics to wave approach angles, likely modulated by local bathymetric features and structural configurations at the port entrance (Fig. 3c and e, respectively).

In addition, the monthly distribution of extreme wave-induced agitation was assessed areas over an 11-year period (2014–2024), as shown in Fig. 3g–h. A pronounced seasonal signal was evident in Langosteira harbour, with peak exceedance frequencies occurring during the boreal winter months (Fig. 3g). Specifically, January through March exhibit the most severe agitation conditions: cumulative exceedance percentages over the 3-month period reached approximately 57%, 61%, and 68% of total hours above the P90, P95, and P99 thresholds, respectively. As the annual cycle advances, a marked decline in exceedance frequency is observed, reaching near-negligible levels between June and August. This attenuation coincides with the seasonal minimum in offshore wave energy flux. From September onwards, there is a gradual resurgence in the frequency of agitation exceedance, with a secondary peak observed in October through December. This bimodal distribution suggests that, in addition to the primary forcing by winter storm activity, transitional swell events and associated synoptic-scale disturbances during the late autumn months contribute substantially to Langosteira harbour agitation.

By contrast, the monthly distribution at Tarragona harbour revealed a more evenly spread regime for the extreme agitation (Fig. 3h). High exceedance percentages were evident during the first four months of the year, particularly in March, where the percentages across all thresholds approached 16–17%. Unlike Langosteira harbour, where agitation was heavily concentrated in January and February, Tarragona harbour exhibited a more gradual onset and decay of agitation activity

during the winter-to-spring transition. From June to September, the proportion of hourly agitation exceeding any threshold fell below 5%, marking a seasonal minimum consistent with the calm summer wave climate typical of the western Mediterranean Sea. A second rise in extreme agitation was observed in the final quarter of the year. November and December, in particular, exhibited a high proportion of hours exceeding the P99 threshold, reaching nearly 15%. These outcomes underscore Tarragona harbour's sensitivity to storm events, particularly those originating from southern or southeastern sectors, which are known to be energetically effective in exciting agitation in this specific port geometry.

4.3 Remote wave monitoring with two HFR ~~networkssystems~~

A quantitative skill assessment of HFR-derived wave estimates during Storm Louis was performed. In the NWI region, time series from the ~~VILA~~Villano-site and the Villano-Sisargas deep-water buoy exhibited strong visual agreement throughout the extreme event (Fig. 4a). The correlation coefficient for SWH is high ($R = 0.92$), with a RMSE of 0.96 m, indicating a high degree of coherence. Both sensors captured the initial wave growth from 21 February, the primary energy peak between 24–25 February, and a secondary crest around 26–27 February. ~~VILA~~Villano-site slightly overestimated SWH maxima relative to the buoy, particularly during the storm's mature phase, although both records converge during the storm's decay stage. The concurrent wave period time series in NWI area showed moderate agreement ($R=0.66$, Fig. 4b), with the HFR-derived CWP and buoy PWP estimates both resolving the rise to values above 14 s during the 21–22 February surge, a brief drop around 23 February, and a sustained 13–15 s regime during the storm's main phase. The HFR data tend to smooth out high-frequency fluctuations, leading to an underestimation (~ 1 s) of the maximum buoy-reported wave periods (16–17 s), and an overestimation during the waning stage of the storm. It is worth mentioning that SeaSonde HFR ~~networkssystems~~ measure a wave period (CWP) that represents the centroid of the model being fitted to the second-order Doppler spectrum (Lipa and Nyden, 2005). Thus, HFR centroid periods dropped always between PWP and MWP collected at Villano-Sisargas buoy. This fact is relevant to properly interpret the skill metrics obtained from comparison, which was conducted against PWP.

By contrast, wave field dynamics in the NEI sector exhibited lower overall energy levels. Both the ~~ALFA~~Alfaeada-site and the Tarragona deep-water buoy recorded relatively calm conditions until 23 February, followed by a marked intensification and a first peak on 26 February. After a rapid decline, a new peak reaching 2.6 m was observed on 28 February (Fig. 4c). Agreement is weaker in this region, with a correlation coefficient of 0.60 and an RMSE of 0.51 m. Wave period estimates in the NEI region (Fig. 4d) demonstrated poorer agreement ($R = 0.34$ and $RMSE = 1.55$ s). The buoy data exhibited pronounced high-frequency variability, with wave periods ranging from 3 to 10 s. However, the HFR-derived CWP was smoother, capturing the dominant 5–8 s wave band during 24–26 February but underrepresenting both short-period (<4 s) and long-period (>9 s) oscillations by up to 2 s.

Overall, the results confirm that HFR ~~networkssystems~~ effectively captured the general evolution and magnitude of extreme storm-induced wave fields, ~~exhibiting consistently higher skill in the estimation of SWH compared to wave period, with consistently higher skill in estimating SWH than wave period.~~ Performance ~~was~~ notably better in the NWI region, ~~where~~

Con formato: Fuente: 10 pto

355 ~~wave energy levels were higher and radar coverage more extensive, likely reflecting the combination of higher incident wave energy and more comprehensive radar coverage. This spatially dependent variability in performance is consistent with the results reported by Saviano et al. (2022), who documented similar HFR–buoy skill contrasts under differing wave energy regimes and bathymetric conditions.~~ These findings underscore both the potential and limitations of HFR technology for real-time wave monitoring under severe weather conditions, particularly in high-energy offshore environments.

360 Additionally, a comprehensive long-term validation of HFR-derived wave parameters provided by ~~VILA~~Villano site was conducted using *in situ* measurements from Villano-Sisargas deep-water buoy over an 11-year concurrent period (2014–2024). The scatter analysis of SWH (Fig. A3a) demonstrated strong agreement between the two sensors, with a significantly high correlation coefficient ($R = 0.87$), a moderately low RMSE of 0.82 m, and a best-fit regression slope near unity (1.02). The negligible intercept (-0.01 m) and close clustering along the 1:1 reference line further confirms the HFR system's
365 ability to capture both the magnitude and variability of SWH over extended timescales. By contrast, the comparison of wave periods (Fig. A3b) yielded a moderate, yet statistically significant, correlation coefficient ($R = 0.71$) accompanied by a higher RMSE of 1.61 s. The best-fit slope of 0.61 and intercept of 4.25 s indicate a systematic divergence between the HFR-derived CWP and the buoy-derived PWP. Specifically, the HFR tends to underestimate high-period events while overestimating lower-period regimes, reflecting inherent methodological differences in how each system resolves wave
370 spectral characteristics. For MWD (Fig. A3c), the scatter distribution is more dispersed, with a reduced slope (0.52), intercept of 135.28° and RMSE of 33.97° . Despite a moderate correlation ($R = 0.66$), the observed bias and compression of the directional range suggest limitations in the angular resolution of the HFR system, particularly at longer ranges where reduced Bragg scattering coherence may degrade directional accuracy.

These outcomes, which are in accordance with previous statistical results reported in the literature (Atan et al., 2015; Long et al., 2011), collectively demonstrate that the ~~VILA~~Villano site provides ~~ed~~ robust long-term estimates of SWH, moderately
375 reliable wave period data, and qualitatively accurate but less precise wave direction estimates. The performance differences across parameters reflect known limitations of HFR ~~networks~~systems in estimating wave direction and longer-period waves, especially under complex sea states or reduced HFR return conditions. ~~Although the unimodal Pierson–Moskowitz spectral model has proven suitable for wind- and swell-dominated conditions, its applicability may be limited in complex met-ocean environments characterized by multimodal sea states (Lipa et al., 2018).~~ It is also important to ~~noteworth mentioning~~ that the ~~substantial separation~~considerable distance between the deep-water buoy ~~locations~~positions and the selected RCs - 22.52 km for HFR-GaliciaNW (Fig. A2a) and 47.39 km for HFR-DeltaEbroNE (Fig. A2b) - ~~constitutes~~represents a potential source of discrepancy that may ~~affect the derived influence the computed~~skill metrics and ~~partially accounts for the observed differences in performances between the two study areas.~~ Moreover, the assumption of spatial homogeneity within each
385 ~~circular RC in CODAR Seasonde~~ HFR systems may further contribute to the observed discrepancies, particularly in intricate coastal environments where pronounced bathymetric variability and wave transformation processes - such as refraction, dissipation and breaking play a dominant role (Wyatt et al., 2005).

5 Conclusions

The projected rise in both the frequency and intensity of extreme extratropical cyclones presents a growing threat to the resilience of European coastal infrastructure (Little et al., 2023). These powerful storm systems can generate severe metocean conditions, including high winds, heavy precipitation, and dynamic sea-level fluctuations. Among the most vulnerable components of coastal infrastructure are ports, which serve as critical hubs in the global maritime transport network and are essential to international trade and economic stability (Verschuur et al., 2022). As mean sea levels continue to rise due to climate change, the impact of storm surges and extreme wave events is expected to intensify. In particular, wave-induced port agitation poses a significant operational hazard, as energetic wave conditions can severely disrupt internal basin dynamics, impair docking maneuvers, and reduce overall port efficiency even in the absence of structural damage. Such phenomena can lead to both temporary and, in some cases, permanent inundation of port facilities, disrupting operations, damaging equipment and structures, and incurring significant economic costs (Verschuur et al., 2023). The combined effect of these hazards underscores the urgent need for adaptive measures and resilient design in coastal and port infrastructure planning.

This study investigates the meteorological and oceanographic features of Storm Louis, a high-impact deep low-pressure system that affected large areas of Western Europe during 22–26 February 2024. This extreme metocean event was characterized by a pronounced Azores High–Icelandic Low dipole pattern, a canonical manifestation of the positive phase of the North Atlantic Oscillation, which imposed an intensified southwest–northeast pressure gradient exceeding $1.7 \text{ Pa}\cdot\text{km}^{-1}$.

This synoptic configuration facilitated persistent and anomalously strong north-westerly wind over the northeastern Atlantic Ocean (with peaks above $17.57 \text{ m}\cdot\text{s}^{-1}$), generating high-energy wave systems (with SWH and MWP values exceeding 8 m and 13 s, respectively) that significantly impacted the western European coastline.

Two Spanish harbours – Langosteira in NWI region and Tarragona in the NEI region - were used as case studies to examine the storm's impact. A multi-platformsensor observational analysis, combining *in situ* observations from four moored buoys and two tide gauges with remotely sensed data from two HFR networkssystems, was performed to evaluate the relationship between open-ocean wave parameters and the wave-induced agitation within the harbour domain. In the NWI (NEI) area, multiple observed wind and wave parameters associated with Storm Louis exceeded the 99.9th (99th) historicalclimatological percentiles, based on the available 11-year observational recordreference period spanning 2014-2024.

The analysis of high frequency sea level oscillations during Storm Louis revealed differences in harbour agitation between Langosteira and Tarragona tide-gauges, despite both exceeding their respective historical P99 thresholds. Langosteira experienced a moderate but prolonged event peaking at 0.68 m, with minimal storm surge influence, while Tarragona underwent a shorter, more intense peak of 1.77 m, also decoupled from storm surge. This heterogeneity in storm response between both harbours may be attributable to i) differences in mouth orientation relative to the predominant incident wave direction; and ii) the contrasting exposure levels of the tide-gauge locations. Specifically, the Tarragona tide gauge is situated in an exposed position at the harbour entrance, at the seaward terminus of the main breakwater (Fig. A1b), which

Con formato: Párrafo de lista;Bullet List Paragraph;Lettre d'introduction;Numbered paragraph 1;Paragrafo elenco;1st level - Bullet List Paragraph;Heading 4 bullet;Paragrafo elenco numerato;Bullet point;Enumeración 2;Bullet Paragraph;List Paragraph1

makes it more susceptible to incoming wave energy. By contrast, the Langosteira tide gauge is located in a more protected position, behind a secondary breakwater (Fig. A1a), resulting in significantly lower agitation levels during the same storm event. This outcome highlights the critical functional role of secondary defensive structures—such as inner or secondary breakwaters—in mitigating wave-induced agitation. Long-term data (2014–2024) showed strong correlations between offshore wave height conditions and harbour agitation ($R = 0.88$ for Langosteira, $R = 0.75$ for Tarragona), though Tarragona port exhibited a more complex, directionally sensitive response. Peak agitation events were predominantly associated with moderate offshore wave heights (below 3 m) propagating from the southernmost sector, underscoring the harbour's marked sensitivity to wave incidence angle and its role in amplifying internal hydrodynamic response. In addition to directional sensitivity -largely controlled by the configuration of the breakwaters and the harbour entrance- other structural features not analysed in this study, such as the basin layout (including basin shape, dimensions, and depth), have also been shown to influence how incoming waves from different directions are transmitted and amplified within the port (Casas-Prat et al., 2012).

Seasonally, agitation in Langosteira harbour was sharply concentrated in winter, especially January–March, with negligible summer activity, whereas Tarragona port displayed a more evenly distributed pattern with notable secondary peaks in late autumn, particularly December. Furthermore, the threshold values defining P90, P95, and especially P99 are significantly higher in Tarragona, indicating that Tarragona port experiences generally higher agitation magnitudes than Langosteira port. This analysis of agitation exceedance over time emphasizes the importance of integrating seasonal variability into port management practices and engineering design frameworks, ensuring that they reflect the fluctuating intensity of metocean forcing throughout the year. The dataset serves as a key resource for quantifying exposure to wave agitation and underpins evidence-based evaluations of harbour operability and long-term infrastructure resilience.

Beyond the event-scale analysis, this study contributes to the broader framework of climate-resilient port management by illustrating how compound metocean hazards and associated wave agitation may compromise critical harbour operations. The impacts observed at Langosteira and Tarragona harbours underscore the need for integrated multi-hazard early warning systems to support anticipatory decision-making and robust, evidence-based assessments of harbour operability. Such approaches align with the objectives of the EU Mission “Ocean and Waters” which promotes the enhancement of long-term infrastructure resilience and the translation of scientific knowledge into operational tools for sustainable ocean governance under a changing climate (EU Mission Ocean and Waters website, 2025).

In addition, the capacity of HFR technology to capture extreme wave conditions was evaluated through direct comparison with *in situ* buoy measurements. Results suggest that HFR networks are capable of reliably characterizing storm-induced offshore wave fields, supporting their broader adoption in operational monitoring frameworks. Complementarily, a long-term (2014–2024) validation of HFR-derived wave parameters from VILA Villano site against *in situ* data from Villano-Sisargas deep-water buoy revealed a strong agreement for SWH ($R = 0.87$), a moderate concordance for CWP ($R = 0.71$) but revealed systematic biases due to methodological differences. MWD showed greater dispersion and reduced accuracy ($R = 0.66$), reflecting well-known HFR limitations such as radio frequency interference under low-wave conditions.

455 The considerable distance between the deep-water buoy locations and the selected RCs (shown in Fig. 2A) should also be
acknowledged, as it may influence the accuracy and interpretation of the derived skill metrics. The sensitivity of wave
parameter estimates to the aforementioned low-frequency noise could be mitigated through the implementation of a multi-
frequency HFR system. By alternating the transmit frequency from 5 MHz to 13 MHz during low to moderate sea states -
typically occurring in NWI during late spring and summer - measurement performance across a broad range of SWH may be
460 substantially improved (Wyatt and Green 2009).
In summary, the present study underscores the importance of integrated observational platforms for real-time extreme hazard
assessment and highlights the critical need to develop climate-resilient port infrastructure capable of withstanding
intensifying ocean-atmosphere extremes.

Data availability

465 The model and observation products used in this study from both the Copernicus Marine Service and other sources are listed
in Table 1.

Author contributions

PL, GA, PM, SG, CPI, MA, VMM, PG, FM, AMM, BPG, SPR and MIR conducted the pilot study through fruitful
discussions in the framework of working team meetings. PL: designed the experiment, analysed the data, created the figures,
470 and prepared a first version of the draft with inputs from all co-authors. MA, SM and CPI: conducted a bibliographic
revision of extreme metocean events previously occurred in the study areas. PG, AMM and MIR: prepared the ERA5
dataset. FM: extracted time series from Puertos del Estado internal database and prepared diverse *in situ* sensors datasets.
BPG: proposed the agitation study in both ports and analysed the corresponding tide-gauge records. SPR: analysed the
atmospheric driving mechanisms during the event. MIR: applied a quality control for historical time series of wave
475 parameters from coastal ~~moored~~ buoys. PM and GA prepared datasets from ~~VILAVillano-radar~~ site, while VMM did so for
the ~~Alfaeada-ALFAradar~~ site. Finally, all authors participated in successive iterations, the drafting and revision of the
manuscript.

Competing interests

The contact author has declared that none of the authors has any competing interests. Disclaimer. Publisher's note:
480 Copernicus Publications remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Acknowledgments

The authors are grateful to the Copernicus Marine Service for the data provision. Finally, the authors are grateful to INTECMAR–Consellería do Mar–Xunta de Galicia and the Hydrographic Institute of Portugal for the strong cooperation to jointly operate the NWI HFR network.

References

AEMET website: Homepage, https://www.aemet.es/es/web/conocerlas/borrascas/2023-2024/estudios_e_impactos/louis, last access: 26 December 2025.

Álvarez-Fanjul, E., Pérez Gómez, B., de Alfonso Alonso-Muñoyerro, M., Lorente Jiménez, P., García Sotillo, M., Lin-Ye, J., Aznar Lecocq, R., Ruiz Gil de la Serna, M., Pérez Rubio, S., Clementi, E., Coppini, G., García-León, M., Fernandes, M.; García Valdecasas, J., García Valdecasas, J.M., Santos Muñoz, D., Luna Rico, M.Y., Mestres, M., Molina, R., Tintorée, J., Mourre, B., Masina, S., Mosso, C., Reyes, E. and Santana, A.: Western Mediterranean record-breaking storm Gloria: An integrated assessment based on models and observations. In: von Schuckmann K. et al. (2022), Copernicus Ocean State Report, issue 6, Journal of Operational Oceanography, pages 1-220, ISSN 1755-876X, doi:10.1080/1755876X.2022.2095169, 2022.

Aon-Benfield: Annual global climate and catastrophe report, [Impact Forecasting](#) 2009. [200 E. Randolph Street, Chicago, Illinois 60601](#), http://www.aon.com/attachments/reinsurance/200912_ab_if_impact_forecasting_2009_report.pdf, last [access:ed 26 December 2025] 18 November 2010].

Asariotis, R., Benamara, H. and Mohos-Naray, V.: Port industry survey on climate change impacts and adaptation UNCTAD Research Paper, 18, 10.13140/RG.2.2.28176.66569, 2017.

Atan, R., ~~J.-Goggins, J.M.~~ Hartnett, ~~M.S.~~ Nash, ~~S.~~ and ~~P.-Agostinho, P.~~: Assessment of Extreme Wave Height Events in Galway Bay Using High Frequency Radar (CODAR) Data.” Renewable Energies Offshore 49–56. doi:10.1201/b18973-8, 2015.

Atan, R., ~~J.-Goggins, J.~~ and ~~S.-Nash, S.~~: A Detailed Assessment of the Wave Energy Resource at the Atlantic Marine Energy Test Site, Energies 9 (11): 967. doi:10.3390/en9110967, 2016.

Barrick, D. E., Evans, M. W., and Weber, B. L.: Ocean surface currents mapped by radar. Science 198, 138–144. doi: 10.1126/science.198.4313.138, 1977.

Basañez, A., Lorente, P., Montero, P., Álvarez-Fanjul, E., and Pérez-Muñuzuri, V.: Quality assessment and practical interpretation of the wave parameters estimated by HF Radars in NW Spain, Remote Sens., 12, 4, 598, <https://doi.org/10.3390/rs12040598>, 2019.

Camus, P., Tomás, A. Díaz-Hernández, G., Rodríguez, B., Izaguirre, C. and Losada, I.J.: Probabilistic assessment of port operation downtimes under climate change, Coastal Engineering, 147, 12-24, doi:10.1016/j.coastaleng.2019.01.007, 2019.

Con formato: Inglés (Reino Unido)

Con formato: Español (España)

Coles, S.: An Introduction to Statistical Modelling of Extreme Values. Springer-Verlag, doi:10.1007/978-1-4471-3675-0, 2001.

Cao, X. and Su, Z. Do Extreme Weather Events Increase Public Concern, Knowledge, and Attention to Climate Change in China? British Journal of Political Science, 55, e10, doi:10.1017/S0007123424000565, 2025.

Casas-Prat, M. and Sierra, J. P.: Trend analysis of wave direction and associated impacts on the Catalan coast, Climatic Change, 115, 667–691, <https://doi.org/10.1007/s10584-012-0466-9>, 2012.

Copernicus Marine In situ Team. Copernicus in Situ TAC, Real Time Quality Control for WAVES. Toulouse, France: Copernicus in situ TAC, 1–16. doi:10.13155/46607, 2020.

Crombie, D. D.: Doppler spectrum of sea echo at 13.56 Mc/S. Nature 175, 681–682. doi: 10.1038/175681a0, 1995.

Davidson, F., Alvera-Azcárate, A., Barth, A., Brassington, G.B., Chassignet, E.P., Clementi, E., De Mey-Frémaux, P., Divakaran, P., Harris, C., Hernandez, F., et al.: Synergies in Operational Oceanography: The intrinsic need for sustained ocean observations, Front. Mar. Sci., 6, 450, doi:10.3389/fmars.2019.00450, 2019.

Díaz-Hernández, G., Rodríguez Fernández, B., Romano-Moreno, E. and Lara, J.L.: An improved model for fast and reliable harbour wave agitation assessment, Coastal Engineering, 170, 104011, doi:10.1016/j.coastaleng.2021.104011, 2021.

Emery, W.J. and Thompson, R.E.: Data Analysis Methods in Physical Oceanography, Elsevier Science, ISBN 9780080477008, 654 pages, Amsterdam, 2001.

EU Copernicus Marine Service Product: Atlantic Iberian Biscay Irish Ocean- In-Situ Near Real Time Observations, Mercator Ocean International [data set], <https://doi.org/10.48670/moi-00043>, 2025.

EU Mission Ocean and Waters website: Homepage, https://oceans-and-fisheries.ec.europa.eu/news/mission-ocean-and-waters-over-1000-initiatives-protect-and-restore-marine-and-freshwater-ecosystems-2025-06-02_en, last access: 26 December 2025.

Fanti, V., Ferreira, Ó., Kümmerer, V. and Loureiro, C.: Improved estimates of extreme wave conditions in coastal areas from calibrated global reanalyses, Commun Earth Environ, 4, 151, doi:10.1038/s43247-023-00819-0, 2023.

Fernández-Pérez, A., Lara, J.L., Lucio, D. and Losada, I.J.: Compound climate change risk analysis for port infrastructures, Coastal Engineering, 193, 104560, ISSN 0378-3839, doi:10.1016/j.coastaleng.2024.104560, 2024.

Fink, A. H., Brücher, T., Ermert, V., Krüger, A., and Pinto, J. G.: The European storm Kyrill in January 2007: synoptic evolution, meteorological impacts and some considerations with respect to climate change, Nat. Hazards Earth Syst. Sci., 9, 405–423, doi:10.5194/nhess-9-405-2009, 2009.

Forzieri, G., Bianchi, A., Batista e Silva, F., Marin Herrera, M.A., Leblois, A., Lavalley, C., Aerts, J.C.J.H., Feyen, L. Escalating impacts of climate extremes on critical infrastructures in Europe, Global Environmental Change, 48, 97-107, doi:10.1016/j.gloenvcha.2017.11.007, 2018.

Forney, R., H-Roarty, H. and S-Glenn, S.: Measuring Waves with a Compact HF Radar. Paper presented at OCEANS 2015 - MTS/IEEE, Washington, 19–22 October 2015.

Con formato: Párrafo de lista;Bullet List Paragraph;Lettre d'introduction;Numbered paragraph 1;Paragrafo elenco;1st level - Bullet List Paragraph;Heading 4 bullet;Paragrafo elenco numerato;Bullet point;Enumeración 2;Bullet Paragraph;List Paragraph1

Con formato: Inglés (Reino Unido)

- García-Valdecasas, J., Pérez Gómez, B., Molina, R., Rodríguez, A., Rodríguez, D., Pérez, S., Campos, A., Rodríguez-Rubio, P., Gracia, S., Ripollés, L., Terrés Nicolí, J.M., de los Santos, F.J. and Álvarez-Fanjul, E.: Operational tool for characterizing high-frequency sea level oscillations, *Nat. Hazards*, 106, 1149–1167, doi:10.1007/s11069-020-04316-x, 2021.
- Harley, M.: Coastal storm definition, In *Coastal storms: processes and impacts*, edited by: Ciavola, P. and Coco, G., John Wiley and Sons, 1-21, doi:10.1002/9781118937099.ch1, 2017, 1–21, Ed. John Wiley & Sons, 2017.
- Hersbach, H., Bell, B., Berrisford, P., Biavati, G., Horányi, A., Muñoz Sabater, J., Nicolas, J., Peubey, C., Radu, R., Rozum, I., Schepers, D., Simmons, A., Soci, C., Dee, D., Thépaut, J.-N.: “ERA5 hourly data on single levels from 1940 to present. Copernicus Climate Change Service (C3S) Climate Data Store (CDS)”, doi: 10.24381/cds.adbb2d47 (last access: 17 June 2025), 2023.
- Hisaki, Y.: Nonlinear inversion of the integral equation to estimate ocean wave spectra from HF radar, *Radio Sci.*, 31, 25–39, <https://doi.org/10.1029/95RS02439>, 1996.
- Hurrell, J.W. and Deser, C.: North Atlantic climate variability: The role of the North Atlantic Oscillation, *J. Mar. Syst.*, 78, 28–41, doi: 10.1016/j.jmarsys.2009.11.002, 2009.
- In Situ* TAC partners: EU Copernicus Marine Service Product User Manual for the Atlantic Iberian Biscay Irish Ocean - In-Situ Near Real Time Observations, INSITU_IBI-PHYBGCWAV_DISCRETE_MYNRT_013_033, Issue: 2.2, Mercator Ocean International, <https://catalogue.marine.copernicus.eu/documents/PUM/CMEMS-INS-PUM-013-030-036.pdf> (last access: 21 July 2025), 2024.
- Izaguirre, C., Losada, I.J., Camus, P. et al.: Climate change risk to global port operations, *Nat. Clim. Chang.*, 11, 14–20, doi:10.1038/s41558-020-00937-z, 2021.
- Jacobeit, J., Philipp, A. and Nonnenmacher, M.: Atmospheric circulation dynamics linked with prominent discharge events in Central Europe. *Hydrological Sciences Journal*, 51(5), 946–965, doi:10.1623/hysj.51.5.946, 2006.
- ~~Jardine, A., Selby, K. and Higgins, D.: A multidisciplinary investigation of Storms Ciara and Dennis, February 2020, International Journal of Disaster Risk Reduction, 90, 103657, doi:10.1016/j.ijdr.2023.103657, 2023.~~
- Kettle, A. J.: Storm Kyrill and the storms of mid-January 2007: Societal and Energy Impacts in Europe, *Adv. Geosci.*, 58, 135–147, <https://doi.org/10.5194/adgeo-58-135-2023>, 2023.
- Kleespies, M.W., Friedrich, T., Marg, O. et al. Assessing the unseen consequences: influence of an extreme weather event on environmental perceptions and connection to nature. *Environ Sci Eur*, 36, 122, doi:10.1186/s12302-024-00950-5, 2024.
- Khodayar, S., Kushta, J., Catto, J. L., Dafis, S., Davolio, S., Ferrarin, C. et al.: Mediterranean cyclones in a changing climate: A review on their socio-economic impacts. *Reviews of Geophysics*, 63(2), e2024RG000853, 2025.
- Konisky, D. M., Hughes, L., and Kaylor, C.H.: Extreme weather events and climate change concern. *Clim. Change*, 134, 533–547, doi: 10.1007/s10584-015-1555-3, 2015.
- Leal Filho, W., Abeldaño Zuñiga, R.A., Sierra, J. et al. An assessment of priorities in handling climate change impacts on infrastructures. *Sci Rep* 14, 14147, doi:10.1038/s41598-024-64606-3, 2024.

Liberato, M. L. R., Pinto, J. G., Trigo, I. F. and Trigo, R. M.: Klaus - an exceptional winter storm over northern Iberia and southern France. *Weather*, 66 (12), 330-334. ISSN 1477-8696, doi:10.1002/wea.755, 2011.

580 Linnenluecke, M. K., Griffiths, A., and Winn, M.: Extreme weather events and the critical importance of anticipatory adaptation and organizational resilience in responding to impacts. *Bus. Strat. Environ.*, 21, 17–32, doi: 10.1002/bse.708, 2012.

Lipa, B. J., and Nyden, B.: Directional wave information from the SeaSonde. *IEEE J. Oceanic Eng.* 30, 221–231. doi: 10.1109/joe.2004.839929, 2005.

585 Lipa, B. J., Nyden, B., Barrick, D., and Kohut, J.: HF Radar Sea-Echo from Shallow Water, *Sensors*, 8, 4611–4635, 2008.

Lipa, B. J., Daugharty, M., Fernandes, M., Barrick, D., Alonso-Martirena, A., Roarty, H., Dicooulos, J. and Whelan, C.: Developments in Compact HF Radar Ocean Wave Measurements. In *Physical Sensors, Sensor Networks and Remote Sensing. Book Series: Advances in Sensors: Reviews, Vol. 5*, edited by S. Yurish, 469–495. Barcelona, Spain: International Frequency Sensor Association Publishing (IFSA), 2018.

590 Little, A.S., Priestley, M.D.K. ~~and~~ Catto, J.L. Future increased risk from extratropical windstorms in northern Europe. *Nat Commun* 14, 4434, doi:10.1038/s41467-023-40102-6, 2023.

Long, R. M., ~~D~~-Barrick, D., ~~J.~~-L. Largier, J.L. and ~~N~~-Garfield, N.: Wave Observations from Central California: SeaSonde Systems and in Situ Wave Measurements. *Journal of Sensors* 2011: 1–18. doi:10.1155/2011/728936, 2011.

Lopez, G. and Conley, D.C.: Comparison of HF Radar Fields of Directional Wave Spectra Against *In Situ* Measurements at

595 Multiple Locations. *Journal of Marine Science and Engineering*, 7(8), 271, doi:10.3390/jmse7080271, 2019.

Lorente, P., Aguiar, E., Bondoni, M., Berta, M., Brandini, C., Cáceres-Euse, A., Capodici, F., Cianelli, D., Ciraolo, G., Corgnati, L., Dadic, V., Doronzo, B., Drago, A., Dumas, D., ´ Falco, P., Fattorini, M., Gauci, A., Gómez, R., Griffa, A., Guérin, C.-A., Hernández-Carrasco, I., Hernández-Lasheras, J., Licer, ´ M., Magaldi, M. G., Mantovani, C., Mihanovic, H., Molcard, A., ´ Murre, B., Orfila, A., Révelard, A., Reyes, E., Sánchez, J., Saviano, S., Sciascia, R., Taddei, S., Tintoré, J., Toledo, Y., Ursella, L., Uttieri, M., Vilibic, I., Zambianchi, E., and Cardin, V.: Coastal ´ high-frequency radars in the Mediterranean – Part 1: Status of operations and a framework for future development, *Ocean Sci.*, 18, 761–795, doi:10.5194/os-18-761-2022, 2022.

600 Lorente, P., de Alfonso, M., Gil, P., Manzano, F., Matulka, A. M., Pérez-Gómez, B., Pérez-Rubio, S., and Ruiz, M. I.: Monitoring the record-breaking wave event in Melilla harbour (SW Mediterranean Sea), in: 8th edition of the Copernicus Ocean State Report (OSR8), edited by: von Schuckmann, K., Moreira, L., Grégoire, M., Marcos, M., Staneva, J., Brasseur, P., Garric, G., Lionello, P., Karstensen, J., and Neukermans, G., Copernicus Publications, State Planet, 4-osr8, 19, <https://doi.org/10.5194/sp-4-osr8-19-2024>, 2024.

Lucio, D., Lara, J.L., Tomás, A. and Losada, I.J.: Probabilistic assessment of climate-related impacts and risks in ports, *Reliability Engineering and System Safety*, 251, 110333, ISSN 0951-8320, doi:10.1016/j.ress.2024.110333, 2024.

Con formato: Fuente: 10 pto

610 Pérez-Gómez, B., A. Payo, D. López, P.L. Woodworth and E. Alvarez-Fanjul: Overlapping sea level time series measured
using different technologies: an example from the REDMAR Spanish network, *Nat. Hazards Earth Syst. Sci.*, 14, 589-610,
2014.

Mateos, R. M., Sarro, R., Díez-Herrero, A., Reyes-Carmona, C., López-Vinielles, J., Ezquerro, P., and Monserrat, O.:
Assessment of the socio-economic impacts of extreme weather events on the coast of southwest Europe during the period
615 2009–2020. *Applied Sciences*, 13(4), 2640, 2023.

Mohr, S., Wilhelm, J., Wandel, J., Kunz, M., Portmann, R., Punge, H.J., Schmidberger, M., Quinting, J.F. and Grams, C.M.:
The role of large-scale dynamics in an exceptional sequence of severe thunderstorms in Europe May–June 2018. *WCD*
1:325–348, doi:10.5194/wcd-1-325-2020, 2020.

Morales-Márquez, V., Orfila, A., Simarro, G., ~~and~~ Marcos, M.: Extreme waves and climatic patterns of variability in the
620 eastern North Atlantic and Mediterranean basins, *Ocean Sci.*, 16, 1385–1398, doi:10.5194/os-16-1385-2020, 2020. ~~Ocean~~
~~Science Discussions~~, 2020, 1–21, 2020.

Morales-Márquez, V., Dumas, D. and Guérin, C.A.: HF radar estimation of ocean wave parameters: Second-order Doppler
spectrum versus Bragg wave modulation approach, *Coastal Engineering*, 198, 104719, ISSN 0378-3839,
doi:10.1016/j.coastaleng.2025.104719, 2024.

625 Owen, L.E., Catto, J.L., Stephenson, D.B., Dunstone, N.J.: Compound precipitation and wind extremes over Europe and
their relationship to extratropical cyclones, *Weather and Climate Extremes*, 33, 100342, doi:10.1016/j.wace.2021.100342,
2021.

Portillo Juan, N., Negro Valdecantos, V., and del Campo, J. M.: Review of the Impacts of Climate Change on Ports and
Harbours and Their Adaptation in Spain, *Sustainability*, 14, 7507, doi:10.3390/su14127507, 2022.

630 Piñeres-Castillo, A.P. and Mojica-Herazo, J.C: A Review of Wind Impact on Container Port Operations: Current
Technologies, Strategies and Future Perspectives. The 2nd International Symposium on Intelligent Systems and Future
Networks (ISFN 2024) October 28-30, 2024, Leuven, Belgium. *Procedia Computer Science*, 251, 783–788, 2024.

Roarty, H., Cook, T., Hazard, L., George, D., Harlan, J., Cosoli, S., et al.: The Global High Frequency Radar Network.
Front. Mar. Sci. 6:164. doi: 10.3389/fmars.2019.00164, 2019.

635 Romano-Moreno, E., Diaz-Hernandez, G., Lara, J. L. Tomás, A., and Jaime, F. F.: Wave downscaling strategies for practical
wave agitation studies in harbours, *Coast. Eng.*, 175, 104140, ~~https://doi.org/~~doi:10.1016/j.coastaleng.2022.104140, 2022.

Rubio, A., Mader, J., Corgnati, L., Mantovani, C., Griffa, A., Novellino, A., et al.: HF radar activity in European coastal
seas: next steps towards a panEuropean HF radar network. *Front. Mar. Sci.* 20:8. doi: 10.3389/fmars.2017. 00008, 2017.

Sánchez-Arcilla, A., Sierra, J.P., Brown, S., Casas-Prat, M., Nicholls, R.J., Lionello, P., and Conte, D.: A review of potential
640 physical impacts on harbours in the Mediterranean Sea under climate change, *Reg. Environ. Change*, 16, 2471–2484,
doi:10.1007/s10113-016-0972-9, 2016.

Con formato: Fuente de párrafo predeter.

Con formato: Fuente de párrafo predeter.

Saviano, S., Biancardi, A. A., Uttieri, M., Zambianchi, E., Cusati, L.A., Pedroncini, A., Contento, G., and Cianelli, D.: *Sea Storm Analysis: Evaluation of Multiannual Wave Parameters Retrieved from HF Radar and Wave Model*. *Remote Sens.* **2022**, *14*, 1696, doi:10.3390/rs14071696, 2022.

Sierra, J. P., Casas-Prat, M., Virgili, M., Möso, C., and SánchezArcilla, A.: Impacts on wave-driven harbour agitation due to climate change in Catalan ports, *Nat. Hazards Earth Syst. Sci.*, **15**, 1695–1709, <https://doi.org/10.5194/nhess-15-1695-2015>, 2015.

Sierra, J.P., Sánchez-Arcilla, A., Gironella, X., Gracia, V., Altomare, C., Möso, C., González-Marco, D., Gómez, J., Barceló, M. and Barahona, C.: Impact of climate change on berthing areas in ports of the Balearic Islands: adaptation measures. *Front. Mar. Sci.* **10**:1124763. doi: 10.3389/fmars.2023.1124763, 2023.

Tian, Z., Wen, B., Jin, L., and Tian, Y.: Radio frequency interference suppression algorithm in spatial domain for compact high-frequency radar, *IEEE Geosci. Remote Sens. Lett.*, **15**, 102–106, 2017.

Tintoré, J., Pinardi, N., Álvarez-Fanjul, E., et al.: Challenges for Sustained Observing and Forecasting Systems in the Mediterranean Sea, *Front. Mar. Sci.*, **6**, 568, doi:10.3389/fmars.2019.00568, 2019.

Verschuur, J., Koks, E.E. and Hall, J.W.: Ports' criticality in international trade and global supply-chains, *Nat. Commun.*, **13**, 4351, doi:10.1038/s41467-022-32070-0, 2022.

Verschuur, J., Koks, E.E., Li, S. et al.: Multi-hazard risk to global port infrastructure and resulting trade and logistics losses, *Commun Earth Environ*, **4**, 5, doi:10.1038/s43247-022-00656-7, 2023.

Wanner, H., Beck, C., Brázdil, R., Casty, C., Deutsch, M., Glaser, R., Jacobeit, J., Luterbacher, J., Pfister, C., Pohl, S., Sturm, K., Werner, P. C. and Xoplaki, E.: Dynamic and socioeconomic aspects of historical floods in Central Europe. *Erdkunde*, **58**(1), 1–16, <http://www.jstor.org/stable/25647628>, 2004.

Wehde, H., Schuckmann, K.V., Pouliquen, S., Grouazel, A., Bartolome, T., Tintoré, J., De Alfonso Alonso-Muñoyerro, M., Carval, T., Racapé, V. and the INSTAC team: EU Copernicus Marine Service Quality Information Document for the Atlantic Iberian Biscay Irish Ocean- In-Situ Near Real Time Observations,

INSITU_IBI_PHYBGCWAV_DISCRETE_MYNRT_013_033, Issue 2.4, Mercator Ocean International, <https://catalogue.marine.copernicus.eu/documents/QUID/CMEMS-INS-QUID-013-030-036.pdf> (last access: 17 June 2025), 2024.

Velpuri, M., Das, J. and Umamahesh, N.V. Spatio-temporal compounding of connected extreme events: Projection and hotspot identification, *Environmental Research*, **235**, 116615, doi:10.1016/j.envres.2023.116615, 2023.

Wyatt, L.R.: The Measurement of the Ocean Wave Directional Spectrum from HF Radar Doppler Spectra.” *Radio Science* **21**: 473–485. doi:10.1029/RS021i003p00473, 1986.

Wyatt, L. R.: *A Relaxation Method for Integral Inversion Applied to HF Radar Measurement of the Ocean Wave Directional Spectrum*, *International Journal of Remote Sensing*, **11** (8): 1481–1494, doi:10.1080/01431169008955106, 1990.

Wyatt, L. R., G-Liakhovetski, G.H.-C. Graber, H.C. and B.-K. Haus, B.K.: Factors Affecting the Accuracy of SHOWEX HD Radar Wave Measurements, *J. Atmos. Ocean. Tech.*, **22**, 847–859, <https://doi.org/10.1175/JTECH1728.1>, 2005.

Con formato: Fuente: 10 pto

Con formato: Fuente: 10 pto

Wyatt, L. R., and J.J.Green, J.J.: Measuring High and Low Waves with HF Radar.” In Proceedings of OCEAN_EUROPE, 1–5. Bremen, Germany, May 11–14. doi:10.1109/OCEANSE.2009.5278328, 2009.

Tables

Product ref. No.	Product ID & type	Data access	Documentation
1	ERA5 global reanalysis, numerical models	Hersbach et al. (2023)	Copernicus Climate Change Service, Climate Data Store, (2023): ERA5 hourly data on single levels from 1940 to present. Copernicus Climate Change Service (C3S) Climate Data Store (CDS), DOI: 10.24381/cds.adbb2d47 (last access: 21 July 2025)
2	INSITU_IBI_PHYBGCWAV_DI SCRETE_MYNRT_013_033, in situ observations	EU Copernicus Marine Service Product (2024)	PUM: In situ TAC partners (2024) QUID: Wehde et al. (2024)
3	2 Hz data, high frequency sea level oscillations and agitation parameters from tide gauges, in situ observations	Puertos del Estado website: https://portus.puertos.es , last access: 21 July 2025. Puertos del Estado website: https://portuscopia.puertos.es/Catalog , last access: 21 July 2025.	García-Valdecasas et al. (2021) Product description: https://bancodatos.puertos.es/BD/informes/INT_3.pdf , last access: 21 July 2025.
4	30-minute wave estimations provided by High Frequency radars, remote observations	Puertos del Estado website: https://portus.puertos.es , last access: 21 July 2025. Puertos del Estado website: https://portuscopia.puertos.es/Catalog , last access: 21 July	Product description: https://bancodatos.puertos.es/BD/informes/INT_6.pdf , last access: 21 July 2025.

Código de campo cambiado

Código de campo cambiado

		2025.	
--	--	-------	--

680 **Table 1.. Products from the Copernicus Marine Service and other complementary datasets used in this study, including the Product User Manual (PUM) and Quality Information Document (QUID). For complementary datasets, the link to the product description, data access and scientific references are provided. Last access for all web pages cited in this table: 1 May 2025.**

Source (Product ref. No.)	Type	Location (coverage)	Variable (unit)	Temporal resolution	Time span used	Spatial resolution
Numerical Model (1)	ERA5 reanalysis	Regional domain (40°W - 20°E 20°N - 70°N)	SLP (Pa)	Daily	February 2024	0.25°
			W10 (m·s ⁻¹)			0.25°
			SWH (m)			0.5°
			MWD (°)			0.5°
<i>In situ</i> sensor (2)	Buoy	Coastal locations	SWH (m)	Hourly	2014-2024	Point-wise location
			MWP (s)			
			PWP (s)			
			MWD (°)			
			SWH (m)			
			MWP (s)			

In situ sensor (3)	Buoy	Deep-water locations	PWP (s)	Hourly	2014-2024	Point-wise location
			MWD (°)			
			SLP (Pa)			
			W10 (m·s ⁻¹)			
In situ sensor (4)	Tide gauge	Port location	Sea level (m)	Hourly	2014-2024	Point-wise location
			Agitation (m)			
Remote sensor (5)	HFR	Coastal and deep-water locations	SWH (m)	Hourly	2014-2024	Concentric arcs: 5.1 km wide for HFR-GaliciaNW, 1.66 km wide for HFR-DeltaEbroNE
			CWP (s)			
			MWD (°)			

Table 2. Complementary information about the data sources used in this study. The temporal resolution column corresponds to the processed datasets employed in the analysis and do not reflect the native resolution of the original, raw data. SLP, W10, SWH, MWP, PWP, CWP and MWD stand for sea level pressure, wind at 10 m height, significant wave height, mean wave period, peak wave period, centroid wave period and incoming mean wave direction, respectively.

Buoy	Villano-Sisargas	Langosteira	Tarragona	Tarragona
Study area	1 (NWI)	1 (NWI)	2 (NEI)	2 (NEI)
Type of buoy	Deep-water	Coastal	Deep-water	Coastal

Type of sensor	SeaWatch	WatchMate	SeaWatch	Triaxys
Longitude	9.21°W	8.56°W	1.47°E	1.19°W
Latitude	43.50°N	43.35°N	40.69°N	41.07°N
Depth	386 m	60 m	688 m	15 m
First deployment	May 1998	June 2013	August 2004	November 1992
Parameters	directional waves temperature salinity currents wind atmospheric pressure	directional waves temperature	directional waves temperature salinity currents wind atmospheric pressure	directional waves temperature

Table 3. Technical description of the four *in situ* moored buoys used in the present study.

695

Tide-gauge	Langosteira	Tarragona
Type (manufacturer)	Radar (MIROS)	Radar (MIROS)
First deployment	November 2012	May 2011
Owned by	A Coruña port authority	Tarragona port authority
Operated and maintained by	Puertos del Estado	Puertos del Estado
Longitude	8.53°W	1.21°W
Latitude	43.35°N	41.08°N
Location	At the end of the breakwater, protected by an inner breakwater	At the end of the breakwater, non- protected by an inner breakwater
Parameters	Sea level, agitation and infragravity waved	Sea level, agitation and infragravity waved
Frequency of sampling	2-Hz	2-Hz

Table 4. Technical description of the two tide-gauges used in the present study.

HFR networks	HFR- <u>GaliciaNW</u>	HFR- <u>DeltaEbroNE</u>
--------------	-----------------------	-------------------------

700

Type of radar	CODAR SeaSonde	CODAR SeaSonde
'Direction of arrival' method	Direction-finding	Direction-finding
Number of sites (name: from north to south)	5 (PriorPRIO, VILAVillano, FISTFinisterre, SILLilleiro and LPROLeça-de Palmeira)	3 (SALOSaleu, ALFAAlfacada and VINAVinarez)
First deployment	July 2010	December 2013
Operated by	Puertos del Estado Intecmar Portuguese Hydrographic Institute	Puertos del Estado Magrama Acuamed
Frequency (MHz)	4.4686 (and 13.5 MHz for Leça de Palmeira)	13.5
Bandwidth (KHz)	29.41	90.67
Time resolution of wave data	30 minutes	30 minutes
Site selected in this work	VILAVillano	ALFAAlfacada
Number of range cells	5	7
Range cell selected	4	3
Saturation (upper) limit (m)	21.41	7.07

Table 5. Technical description of the two High Frequency Radar (HFR) systems used in the present study. Official names registered in the European HFR Node are shown.


Con formato: Inglés (Reino Unido)

Con formato: Español (España)

Con formato: Español (España)

Con formato: Español (España)

Figures











Figure 1. (a-c) Synoptic-scale meteocean conditions during storm Louis as derived from ERA5 -product ref. no. 1 (Table 1)-: daily maps of sea level pressure (SLP), wind at 10 m height (W10) and significant wave height (SWH) for 23 February 2024 (peak intensity of Storm Louis); (d-e) Study areas: northwestern Iberia (NWI) and northeastern Iberia (NEI) regions, respectively. The location of each ocean sensor -product ref. no. 2, 3 and 4 (Table 1)- employed in this work is depicted. Orange squares, green diamonds and white dots denote the location of moored buoys, tide gauges and High-Frequency radar (HFR) sites, respectively. Red boxes denote harbour's location. Isobath depths are



730 **Figure 3.** Hourly time series of storm surge (meteorological residual) and port wave agitation (product ref. no. 3 in Table 1) recorded during Storm Louis (20–29 February 2024) by (a) Langosteira and (b) Tarragona tide-gauges (Fig. 1A). The 99th percentile (P99) thresholds for agitation are indicated by dashed red lines. Scatter plots relating port

agitation (product ref. no. 3 in Table 1) to coastal wave conditions (product ref. no. 2 in Table 1) during the 2014-2024
period for: Langosteira (c-d) and b) Tarragona harbour (e-f). Hourly data from Langosteira coastal buoy and
Langosteira tide-gauge were used for Langosteira harbour (NWI area), while hourly observations from Tarragona
coastal buoy and Tarragona tide-gauge were employed for Tarragona harbour (NEI area). Statistical metrics are
adhered in the white boxes. Monthly distribution of extreme port agitation (product ref. no. 3 in Table 1) events from
2014 to 2024, expressed as the percentage of hours exceeding the 90th (P90), 95th (P95) and 99th (P99) percentiles in (g)
Langosteira and (h) Tarragona harbours.






Figure 4. Comparison of hourly estimations of offshore significant wave height (SWH, left panels) and centroid/peak wave period (CWP/PWP, right panels) provided by High-Frequency radar (HFR) sites (product ref. no. 4 in Table 1) against *in situ* buoy observations (product ref. no. 2 in Table 1) during Storm Louis, in the northwestern Iberia (NWI; top panels) and northeastern Iberia (NEI; bottom panels) areas. Hourly data from Villano-Sisargas deep-water buoy and VILA site were used for NWI area, while hourly observations from Tarragona deep-water buoy and ALFA site were employed for NEI area. Statistical metrics are adhered in the grey boxes. For the sake of proper interpretation and comparison, the reader should note that the y-axis scales differ between NWI area and NEI area.






Figure A1. Aerial snapshot showing the geometry of two Spanish harbours: (a) Langosteira harbour (which belongs to A Coruña port authority), located in the northwestern Iberia (NWI) area and (b) Tarragona harbour, situated in

the northeastern Iberia (NEI) area. Orange squares and green diamonds denote the location of coastal moored buoys and tide gauges, respectively. Map by © ArcgGis.

a) HFR-NWI: Range Cells (RC)



b) HFR-NEI: Range Cells (RC)









Figure A2. Spatial distribution of the concentric range cells (RC) extending radially from the onshore origin at (a) the VILAVillano site (HFR-GaliciaNWI system) and (b) the ALFAAlfaada site (HFR-DeltaEbroNEI system). Wave data derived from HFR - product ref. no. 4 in Table 1- for the selected RC (highlighted in red) were compared with *in situ* measurements (product ref. no. 2 in Table 1) from moored buoys (indicated by orange squares). Isobath depths are labelled every 100 m. Distances between moored buoys, their respective sites and selected RCs are shown in the lower boxes.






Figure A3. Long-term skill assessment of VILA site wave data at range cell 3 (RC3) -product ref. no. 4 in Table 1- against *in situ* observations provided by Villano-Sisargas deep-water buoy -product ref. no. 2 in Table 1- for the concurrent 11-year period (2014-2024): best linear fit (solid red line) of scatter plot between hourly observations of a) significant wave height (SWH), b) period (centroid and peak wave period -CWP and PWP, respectively-) and c)

mean wave direction (MWD), where angles less than 60° were adjusted by adding 360° to improve visibility and facilitate linear regression. The dotted black line represents the result of perfect agreement with slope 1.0 and intercept 0. Statistical metrics are presented in the grey box.